

Coil Roofing Nailer



YRN45

Applications

Roofing, Shingle Installation

Specifications

Diameter	.120
Nail Range	3/4" to 1-3/4"
Capacity	120 Nails
Firing Mode	Selectable
Dimensions	10-1/4" x 4" x 11"
Weight	5 lbs
Air Pressure	80-100 p.s.i.

Features

360° Adjustable Exhaust,
Adjustable Depth Control, Easy
Maneuverability, Nail Basket,
Rubber Grip For Comfort

Includes

Tool Oil, Manual, Parts Diagram



For best results, use Spotnails® collated fasteners

Coil Roofing Nails

Stock No.	Length	Description	M/ Cs	Lbs/ Cs	Cs/ Skid
CRN08G	1"	Galvanized	7.2	24.90	56
CRN10G	1-1/4"	Galvanized	7.2	31.60	48
CRN12G	1-1/2"	Galvanized	7.2	38.10	40
CRN14G	1-3/4"	Galvanized	7.2	45.60	40

304 Stainless Steel

CRN10SSR-3.6M	1-1/4"	304 SS, Ring, Dia. Cone	3.6	19.00	48
CRN12SSR-3.6M	1-1/2"	304 SS, Ring, Dia. Cone	3.6	20.00	48
CRN14SSR-3.6M	1-3/4"	304 SS, Ring, Dia. Cone	3.6	23.50	48

Division of Peace Industries, LTD.

Phone: 800-873-2239 ** Fax: 888-369-2588

www.spotnails.com

